Update Tool Introduction for

**CARECAR®** Auto Esys Troubleshooter

Please follow the instruction to upgrade software to your scanner by using AET-I Update Tool.

Open website: updata.carecartool.com Login as product user User Login close or Esc Key Username : 680130003260 Password : •••••• UserType : Product_users v Login Step 2. Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software.	<u>Step 1.</u>	
Login as product user     User Login     Close or Esc Key     Username :   680130003260   Password :   •••••••   UserType :   Product_users *   Login     Step 2.   Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software.   DownLoad   Cookie	Open website: updata.carecartool.com	
User Login close or Esc Key   Username : 680130003260   Password : ••••••   UserType : Product_users •   Login Login   Step 2. Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software. DownLoad DownLoad Cookie	Login as product user	
Username : 680130003260 Password : •••••• UserType : Product_users v Login Step 2. Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software. DownLoad Cookie	User Login	close or Esc Key
Step 2. Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software. DownLoad Cookie	Username : 680130003260 Password : ••••• UserType : Product_users v Login	
Download the "Update Tool" to your local computer and decompress the file Click "Update Tool" to run the software.	<u>Step 2.</u>	
Click "Update Tool" to run the software.	Download the "Update Tool" to your local con	mputer and decompress the file
DownLoad	Click "Update Tool" to run the software.	
	🍌 DownLoad	
	Cookie	

🛃 UpdateTool

<u>Note</u>: Please remove the SD card from your scanner and connect with your computer. Then run the Update Tool. You may see following picture.

### **CARECAR International Inc**



<u>Note</u>: please make sure the serial number show on the **Select device** is same as the serial number you are using. If no serial number or the serial number is not correct, please restart the update tool.

Login and it will show "Checking Updates Version", like following picture.

# **CARECAR International Inc**

pe	Vehicle brand	Lang	Vehicle s	Latest v	Status	^	1.Input user n	ame and password
	updateshow	EN	V02.14				Ilcer Name	600100000000
	audi	AR	V20.05				OSCI Maine	000130003200
	audi	EN	V20.05					
	audi	FR	V20.05				Password	*****
	austford	EN	V20.00					
	benz	AR	V20.16					save information 🕑
]	benz	EN	V20.16				2 Select devi	ce.
	benz	FR	V20.16				2. 301001 0041	uc
	bmw	AR	V20.02					680130003260
]	bmw	EN	V20.02					000130003200
]	bmw	FR	V20.02				- Provide to Provide the Provide State	
]	byd	EN	V20.02				Status into.	
]	changan	EN	V19.05					
]	changchengzy	EN	V19.06					
]	chrysler	AR	V20.10					
]	chrysler	EN	V20.10					
	chrysler	FR	V20.10					
	chzy	EN	V19.05					
]	citroen	AR	V20.01			~		
]			ШГ.		J°1	>		
	R	Checking upd version	lates					D Exit

Click "Checking updates version" and the tool will detect the newest version software automatically.

me 680130003260 rord ●●●●●● Save information ✓ evice 680130003260 ✓
rord Save information revice
rord Save information evice 680130003260
Save information save information evice 680130003260
Save information v evice 680130003260 v
evice 680130003260
evice 680130003260
680130003260
680130003260 🗸
fo
king updates" version is finished!
<b>A</b>
Exit

www.carecartool.com

Email: <a href="mailto:sales@carecartool.com">sales@carecartool.com</a>Tel: +1-917 6218 045

AR

EN

📃 benz

benz

V20.16

V20.17

Save information 🗹

X

2. Select device

Click "Download and update" and the Update Tool will upgrade software automatically.

<u>Note</u>: Please make sure the SD card reader is well connected with your computer.

0	Vehicle	Lang	Vehicle	Late	Status	1.Input user name and password
	audi	EN	V20.05			
	audi	FR	¥20.05			User Name 680130003260
	austford	EN	V20.00			
	benz	AR	V20.16	V20.17		Password
*	benz	EN	V20.16	V20.17	Update finish	
	benz	FR	V20.16	V20.17		Save information
	bmw	AR	V20.02	V20.03		2 Select device
~	bmw	EN	V20.02	V20.03	Start to update	E. OFICE UCTICE
	bmw	FR	V20.02	V20.03		680130003260
	byd	EN	¥20.02			00010000000
	changan	EN	V19.05			Status info
	changch	EN	V19.06			otatus mio.
	chrysler	AR	V20.10	V20,12		
	chrysler	EN	V20.10	V20.12		Download finish, wait to update
	chrysler	FR	V20.10	V20.12		
	chzy	EN	V19.05			
	citroen	AR	V20.01			File bmw_V20.03_EN Retreshing,
	citroen	EN	¥20.01			
_	citroen	FR	¥20.01			×
		Dov	mload and up	date	eded number of vehicle :	softwares to update:2
o:Ilw	ww.carecartoo	l.com			Updated vehicle soft	ware number:1 CARECAR INTERNATIO
n a	ll the so	ftware	update	finish,	please click "O	K" and "Exit".
	AET				Professi	onal Auto Esys Troubleshoot
~	Vehicle	Lang	Vehicle	Late	Status	1.Input user name and password
0	51400		U02 14			and the state of the
	updates	EN	VU2.14			Lloss Name Contangences

benz FR V20.16

Update is finished, re-start the tool to activate the update, there need a few seconds to update when re-starting the tool, please wait until it appears start interface, do not cut off power during this period!

		(	Checking updates version	D Exit	
T			(10)		
	citroen	AR	V20.01	-	
	chzy	EN	V19.05		
	chrysler	FR	V20.10		

#### Option 2 ---- "Update through Local"

If you only want to upgrade one or two software, you can download the software from our website first and then update through local computer.

Login as product user on our website : updata.carecartool.com

Choose the software you want to download and then click "**Download**", like following picture.



Run "Update Tool" and make sure your SD card reader is well connected with computer.

Note: Do not decompress the software.

Please click "Update through local"

### **CARECAR International Inc**



Browse and choose the downloaded file.



www.carecartool.com

Tel: +1-917 6218 045

<u>Note</u>: Please make sure the serial number on **Select device** is same as the diagnostic tool you are using to upgrade.

Then the Update Tool will show your selected software and waiting to be upgraded.

Select the software and click "Start update".

	<ol> <li>Select folder of update file</li> </ol>		
[	C:\Documents and Set	tings\user\Desktop	Browse.
Update info.	2. Select device		
Update software version: V20.00	680130003260	~	
Rest space after update: 2744488 KB	3. Select update file		Select all
Update procedure	BMW V20.03 All Systems BMW V20.03 All Systems Special Function V20.00		
a.Download vehicle software to update tool, website http://www.carecartool.com b.Pull out SD card from tool and plug it in PC-SD car slot.	22 1		
o.Select update software. Select needed vehicle bra and version to update.	ind		
d. Confirm and click 'start update' button to finish update. Note: after update the tool, must re-start the tool.	*		
ent software version 3.0 is supporting AET update			
		Eva	

The Update Tool will upgrade software automatically.

AET	Professional Auto Esys	Troubleshoote
	1. Select folder of update file	
5	C:\Documents and Settings\user\Desk	top Browse
Update info.	2. Select device	
Update software version; V20.	<sup>00</sup> 680130003260 ·	
Space needed for update 1143	31 KB 31 Select undate file	
Rest space after update: 2744		Select all
pdate tool		
Update is finished, re-start the t start interface,do not cut off po	col to activate the update, there need a few seconds to update when re-start wer during this period!	ing the tool, please wait until it
Update is finished, re-start the t start interface, do not cut off po	cool to activate the update, there need a few seconds to update when re-start wer during this period!	ing the tool, please wait until it .
Update is finished, re-start the t start interface, do not cut off po and version to update.	col to activate the update, there need a few seconds to update when re-start wer during this period! OK	ing the tool, please wait until it
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update	col to activate the update, there need a few seconds to update when re-start wer during this period! OK OK Update when re-start oK	ing the tool, please wait until it
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update update. Note: after update the t tool.	col to activate the update, there need a few seconds to update when re-start wer during this period! OK V button to finish cool, must re-start the	ing the tool, please wait until it
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update update. Note: after update the t tool. urrent software version 3.0 is support	col to activate the update, there need a few seconds to update when re-start wer during this period! OK Update OK Description to finish cool, must re-start the ong AET update	ing the tool, please wait until it a
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update update. Note: after update the t tool. urrent software version 3.0 is support	col to activate the update, there need a few seconds to update when re-start wer during this period! OK Update I button to finish ing AET update Update	ing the tool, please wait until it .
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update update. Note: after update the t tool. urrent software version 3.0 is support	vpdate vpdate the update, there need a few seconds to update when re-start	ing the tool, please wait until it
Update is finished, re-start the t start interface, do not cut off po and version to update. d.Confirm and olick 'start update update. Note: after update the t tool. urrent software version 3.0 is support Start Update status	col to activate the update, there need a few seconds to update when re-start wer during this period! OK Update OK update Update O O O O O O O O O O O O O O O O O O O	Exit

When software upgrade is finished, please Click "OK" and " Exit".

#### Step 4.

#### **Vehicle Software Deletion**

When the vehicle software quantity in your diagnostic tool is too many and it makes your working speed slower, you can choose to delete some old versions of the vehicle software.

Connect your SD card reader with computer.

Run the Update Tool software and click "Vehicle software deletion", like following picture.

Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of update       Image: Select way of update         Image: Select way of	AET	Professional Auto Esys Troubleshooter
D Exit	Select w Note: For a quicker upd a SD card reader	ay of update where through internet where the software deletion the software deletion the software deletion the software deletion the software deletion
		S Exit

Then, it will show all the software in your diagnostic tool.

Please select the ones you do not need.

And click "Vehicle software deletion" on the left bottom.

### **CARECAR International Inc**



The tool will pop-up " Are you sure to delete selected vehicle software?"



Click "Yes" to delete and click "No", you can double select the software you need to delete.

After finishing, please click "Exit".



### Carecar International Inc

Email:sales@carecartool.com

www.carecartool.com

Add: 245 East Main Street, Suite 115, Alhambra, CA 91801, USA

Tel: + 1 – 917 6218 045

www.carecartool.com

Email: <u>sales@carecartool.com</u>

Tel: +1-917 6218 045